

Package: cobbdouglasge (via r-universe)

October 11, 2026

Title Edgeworth Box with Contract Curves

Version 0.0.0.9000

Description A Shiny app to visualize an Edgeworth box with contract curve for the 2x2 exchange model using Cobb-Douglas utility functions.

License Apache License (>= 2)

Imports config, golem, shiny, ggplot2, dplyr, magrittr, pkgload

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Config/pak/sysreqs cmake make libuv1-dev zlib1g-dev

Repository <https://pachadotdev.r-universe.dev>

Date/Publication 2026-09-11 04:26:18 UTC

RemoteUrl <https://github.com/pachadotdev/cobbdouglasge>

RemoteRef HEAD

RemoteSha 1268e4783ca5fd5df6939eb7f89f4fe89f7baa25

Contents

run_app	1
Index	3

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

Description

Run the Shiny Application

Usage

```
run_app(  
  onStart = NULL,  
  options = list(),  
  enableBookmarking = NULL,  
  uiPattern = "/",  
  ...  
)
```

Arguments

onStart	A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global.R file can be used for this purpose.
options	Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app.
enableBookmarking	Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app.
uiPattern	A regular expression that will be applied to each GET request to determine whether the ui should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
...	arguments to pass to golem_opts. See <code>“?golem::get_golem_options”</code> for more details.

Index

`enableBookmarking()`, [2](#)

`run_app`, [1](#)